



CSN 25 1280, DIN 862

Vernier depth caliper ČSN 25 1280, DIN 862

<p>2035</p> 		mm	mm	mm		
	2034	0-150	150	0,02		
	2035	0-200	200	0,02		
	2036	0-300	300	0,02		
	2037	0-500	500	0,02		


CSN 25 1282, DIN 862

Vernier depth caliper with nose ČSN 25 1282, DIN 862

<p>2040</p> 		mm	mm	mm		
	2040	0-150	150	0,02		
	2041	0-200	200	0,02		
	2042	0-300	300	0,02		
	2042.2	0-500	500	0,02		


, DIN 862

Digital depth caliper, DIN 862

<p>2047</p> 		mm	mm	mm		
	2047	0-150	150	0,01		
	2048	0-200	200	0,01		
	2049	0-300	300	0,01		
	2050	0-500	500	0,01		


, ABS, , DIN 862, IP54

Digital depth caliper, data output, ABS, PROFESIONAL, DIN 862, IP54

<p>2050.150</p> 		mm	mm	mm		
	NEW 2050.150	0-150	150	0,01		
	NEW 2050.200	0-200	200	0,01		
	NEW 2050.300	0-300	300	0,01		

, DIN 862


Digital depth caliper, screwed nose, DIN 862

<p>2051</p> 		mm	mm	mm		
	2051	0-150	150	0,01		
	2052	0-200	200	0,01		
	2052.1	0-300	300	0,01		
	2052.2	0-500	500	0,01		



, DIN 862


Digital depth caliper with monobl. nose, DIN 862 RECOMMENDED for certification

2053.2 		mm	mm	mm		
	2053.1	0-150	150	0,01		
	2053.2	0-200	200	0,01		
	2053.3	0-300	300	0,01		
	2053.4	0-500	500	0,01		


, ABS,

DIN 862, IP54

Digital depth caliper with monobl. nose, monolitní tělo, data output, ABS, PROFESIONAL DIN 862, IP54


2052.2.150 		mm	mm	mm		
	NEW 2052.2.150	0-150	150	0,01		
	NEW 2052.2.200	0-200	200	0,01		
	NEW 2052.2.300	0-300	300	0,01		

Digital tyre gauge

1119.10 				mm		
	1119.10	±0,2mm		0-25/1"		

CSN 25 1295 DIN 862


Vernier height gauge ČSN 25 1295 DIN 862

3013 			mm	mm		
	3013		200	0,02		
	3014		300	0,02		
	3015		500	0,02		
	3016		1000	0,02		

Calibration certificate included.

CSN 25 1295.1 DIN 862


Digital height gauge ČSN 25 1295.1 DIN 862

3022 			mm	mm		
	3022		200	0,01		
	3023		300	0,01		
	3024		500	0,01		
	3024.0		600	0,01		
	3024.1		1000	0,01		




25 1277


Forester caliper PN 25 1277

		mm	mm /			
	1161	5	500/255			
	1162	5	800/410			
	1163	5	1000/410			


, **CSN 25 1238 DIN 862**
Vernier caliper with locking screw and depth rod. ČSN 25 1238, DIN 862

		mm	mm /			
	6000	0,02	150/40			
	6000.1	0,05 mm+ffinch	150/40			
	6000.2	0,02 mm+ffinch	150/40		,INOX	
	6000.25	0,02 mm+ffinch	160/40		,INOX	
	6000.26	0,05 mm+ffinch	160/40		,INOX	


, **CSN 25 1238 DIN 862**
Vernier caliper with locking device and depth rod, ČSN 25 1238, DIN 862

		mm	mm /			
	6000.7	0,05 mm+ffinch	100/40			
	6000.3	0,02 mm+ffinch	150/40		,INOX	
	6000.4	0,05 mm+ffinch	150/40		,INOX	
	6000.20	0,02 mm+ffinch	160/40		,INOX	
	6000.21	0,05 mm+ffinch	160/40		,INOX	


, **DIN 862 –**
Vernier caliper with locking screw and depth rod DIN 862 LEFT HAND!

		mm	mm /			
	6000.5	0,05	150/40			

, , **CSN 25 1238, DIN 862**
Vernier caliper with locking screw and depth rod, STAINLESS, TOP QUALITY, ČSN 25 1238, DIN 862

		mm	mm /			
	NEW 6001.15	0,02	150/40			
	NEW 6001.20	0,02	200/50			
	NEW 6001.30	0,02	300/55			

, , **CSN 25 1238, DIN 862**
Vernier caliper with locking screw and depth rod, fine adjustment ČSN 25 1238, DIN 862

		mm	mm /			
	6002	0,02	200/50			
	6003	0,02	300/55			



Marking caliper

	6005.10		mm	mm /			
	6005.10	0,1		150/40			
	6005.15	0,1		200/40			
	6005.20	0,1		250/40			
	6005.25	0,1		300/40			
	6005.50	0,1		200/40			
	6005.55	0,1		400/40			
	NEW 6006.20	0,01		200			
	NEW 6006.1						

, CSN 25 1235 DIN 862

Dial caliper with depth rod, ČSN 25 1235, DIN 862

	6013		mm	mm /			
	6013	0,02		150/40	INOX		
	6013.1	0,02		200/45	INOX		
	6013.2	0,02		300/55	INOX		

CSN 25 1230 (CSN 25 1231), DIN 862

Vernier caliper with locking screw, fine adjustment ČSN 25 1230 (ČSN 25 1231), DIN 862


	6015		mm	mm /			
	6015.100	0,02		500/10071			
	6015.125	0,02		500/125			
	6015.150	0,05		500/150			
	6015.200	0,05		500/200			
	6016.100	0,02		600/100			
	6016.125	0,02		600/125			
	6016.150	0,05		600/150			
	6016.200	0,05		600/200			
	6016.300	0,05		600/300			
	6016.2.125	0,02		800/125			
	6016.2.150	0,05		800/150			
	6016.2.200	0,05		800/200			
	6017.125	0,02		1000/125			
	6017.150	0,05		1000/150			
	6017.200	0,05		1000/200			
	6018.125	0,05		1500/125			
	6018.150	0,05		1500/150			
	6018.200	0,05		1500/200			
	6019.125	0,05		2000/125			
6019.150	0,05		2000/150				
6019.200	0,05		2000/200				
6019.300	0,05		2000/300				
6020.250	0,05		2500/250				

Calibration certificate included.



CSN 25 1230 (CSN 25 1231), DIN 862


Vernier caliper with locking screw, fine adjustment ČSN 25 1230, (ČSN 25 1231), DIN 862

6024.1.125			mm	mm /			
		6024.1.125	0,02	600/125			
		6024.2.150	0,02	800/150			
		6024.3.150	0,05	1000/150			

Calibration certificate included.


CSN 25 1233, (CSN 25 1234), DIN 862

Vernier caliper with upper jaws, locking screw, fine adjustment ČSN 25 1233, (ČSN 25 1234), DIN 862


6022.125			mm	mm			
		6022.100	0,02	500/100			
		6022.125	0,02	500/125			
		6022.150	0,05	500/150			
		6022.0.100	0,02	600/100			
		6022.0.125	0,02	600/125			
		6022.0.150	0,05	600/150			
		6022.1.125	0,02	800/125			
		6022.1.150	0,05	800/150			
		6022.1.200	0,05	800/200			
		6022.2.125	0,02	1000/125			
		6022.2.150	0,05	1000/150			
		6023.1.125	0,05	1500/125			
		6023.1.150	0,05	1500/150			
		6023.1.200	0,05	1500/200			
		6023.2.125	0,05	2000/125			
		6023.2.150	0,05	2000/150			
6023.2.200	0,05	2000/200					

Calibration certificate included.

Digital caliper NO NAME



6040			mm	mm /			
		6040	0,01	150/40			

Digital caliper solar NEW


6040.13			mm	mm /			
		6040.13	0.01	150/40			




DIN 862 Digital caliper DIN 862, BIG DISPLAY - NEW MODEL!

 6040.0  6040.2		mm	mm /			
	6040.0	0,01	81/30			
	6040.2	0,01	150/40		HOLD	
	6041.2	0,01	200/50		HOLD	
	6042.2	0,01	300/60		HOLD	


DIN 862 Digital caliper with output for PC DIN 862

 6040.10		mm	mm /			
	6040.10	0,01	150/40		DIN 862	
	6040.11	0,01	200/50		DIN 862	
	6040.12	0,01	300/60		DIN 862	


(ABS), USB, , DIN 862 Digital caliper (ABS), mini USB, data output, DIN 862

 6041.150		mm	mm /			
	NEW 6041.150	0,01	150/40		dfile DIN 862	
	NEW 6041.200	0,01	200/50		dfile DIN 862	
	NEW 6041.300	0,01	300/60		dfile DIN 862	

(ABS), , IP54, DIN 862 Digital caliper (ABS), data output, PROFESIONAL, IP54, DIN 862

 6042.150		mm	mm /			
	NEW 6042.150	0,01	150/40		0,02 mm	
	NEW 6042.200	0,01	200/50		0,02 mm	
	NEW 6042.300	0,01	300/60		0,03 mm	

PC PC conect

 6040.9						
	NEW 6040.9					
	NEW 6040.91			USB		
	NEW 6040.92			IP65		



, DIN 862

Digital caliper DIN 862

	6043.100	mm	mm /			
	6043.100	0,01	500/100	DIN 862		
	6043.125	0,01	500/125	DIN 862		
	6043.2.100	0,01	600/100	DIN 862		
	6043.3.125	0,01	800/125	DIN 862		
	6043.3.150	0,01	800/150	DIN 862		
	6044.125	0,01	1000/125	DIN 862		
	6044.150	0,01	1000/150	DIN 862		
6045.150	0,01	1500/150	+/-0,11			

Calibration certificate included.

DIN 862

Digital caliper with upper jaws DIN 862

	6043.1.100	mm	mm /			
	6043.1.100	0,01	500/100			
	6043.1.125	0,01	500/125			
	6043.1.150	0,01	500/150			
	6043.4.100	0,01	600/100			
	6043.5.125	0,01	800/125			
	6043.5.150	0,01	800/150			
	6044.1.150	0,01	1000/150			
6045.1.150	0,01	1500/150				

Calibration certificate included.

IP 67

Moisture resistant digital caliper IP 67

	6040.15	mm	mm /			
	6040.15	0,01	150/40	IP67		
	6040.16	0,01	200/50	IP67		
	6040.17	0,01	300/60	IP67		


IP 67 -

Moisture resistant digital caliper IP 67 - PROFESIONAL


	6040.15.150	mm	mm /			
	NEW 6040.15.150	0,01	150/40	IP67		12,2
	NEW 6040.15.200	0,01	200/50	IP67		12,2
	NEW 6040.15.300	0,01	300/60	IP67		12,2




Digital caliper for grooves

6040.51 		mm				
	6040.51	0,01			20-150	


Digital caliper for grooves

6040.52 		mm		mm		
	6040.52	0,01		0-150		

Digital unit – horizontal type


6040.101 		mm	mm			
	6040.21	0,01	150			
	6040.22	0,01	200			
	6040.23	0,01	300			
	6040.24	0,01	400			
	6040.25	0,01	500			
	6040.26	0,01	600			

Digital unit – vertical type



6040.102 		mm	mm			
	6040.31	0,01	150			
	6040.32	0,01	200			
	6040.33	0,01	300			
	6040.34	0,01	400			
	6040.35	0,01	500			
	6040.36	0,01	600			

PVC hobby

Plastic caliper hobby

6050 		mm	mm /			
	6050		150/40	PVC		

Welding gauge

1120.1 	1120.4 		mm		mm	
		1120	0.1	50,60,115,120°	0-20	
		1120.1	0.1	60,70,80,90°	0-20	
		1120.4	0.01	60,70,80,90°	0-20	